


IP-A8DZ

8mp / 4K DOME IP Camera with IR Night Vision, 2.8-12mm Motorized ZoomLens



- H.265+, H.265, H.264+, H.264, MJPEG encoding
- Max. resolution: 8MP / 4K (3840 × 2160)
- Auto day / night-time IR modes
- Built-in IR Night Vision LED
- 2.8-12mm Motorized Zoom Lens w/ Auto-focus
- Built-in Audio Surveillance Microphone
- 30~50m effective distance IR night vision
- PoE and 12V DC power support
- IP67 Weatherproof rating
- Micro SD slot
- Support remote monitoring by mobile app for iPhone and Android mobile apps
- Support P2P function, Connects directly to mobile app, NVR Not required
- Built-in AI software detects people, automobiles, bikes, motorcycles
- AI functions: line crossing detection, region intrusion detection, abandoned/missing object detection, video exception detection
- Dual firmware system backup for disaster recovery



www.Viewtron.com

Viewtron by CCTV Camera Pros

7142 N Seacrest Blvd.
Lantana, FL 33462
United States of America

Tel: +1-561-433-8488
www.Viewtron.com


Fax: +1-800-942-0728
info@cctvcamerapro.net

SPECIFICATIONS

Specifications	Model	IP-A8DZ		
Camera				
Image Sensor	1 / 2.8 "CMOS			
Image Size	3840×2160			
Electronic Shutter	1 / 3 s ~ 1 / 100000 s			
Iris Type	DC Iris			
Min. Illumination	0.015 lux@F1.4, AGC ON; 0 lux with IR			
Lens	2.8~12mm@F1.4, motorized			
Field of View	Horizontal: 102°~32°; Vertical: 54°~17°; Diagonal: 120°~37°			
Lens Mount	Φ14			
Day & Night	ICR			
Wide Dynamic Range	120dB			
BLC	Yes			
HLC	Yes			
Defog	Yes			
S/N Ratio	≥50dB			
EIS	Yes			
Digital NR	3D DNR			
Angle Adjustment	Pan: 0°~360°; Tilt: 0°~80°; Rotation: 0°~360°			
Image				
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG			
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile			
Resolution	8MP (3840 × 2160), 6MP(3072 × 2048), 5MP(2592 × 1944), 4MP(2592 × 1520), 2K (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240, VGA(640×480)			
Main Stream	8MP/6MP/5MP/4MP/2K/3MP/1080P/720P(60Hz:1~30fps; 50Hz:1~25fps)			
Sub Stream	720P/D1/CIF/VGA/480×240(60Hz:1~30fps; 50Hz:1~25fps)			
Third Stream	720P/D1/CIF/480×240(60Hz:1~30fps; 50Hz:1~25fps)			
Bit Rate	64 Kbps ~ 12Mbps			
Bit Rate Type	VBR / CBR			
Audio Compression	G711A / U			
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser			
ROI	Each ROI to be configured separately			
Interfaces				
Network	RJ 45 10M/100M self-adaptive Ethernet port			
Video Output	No			
Audio	1CH audio input; 1CH built-in MIC			
Storage	Built-in micro SD card slot; up to 256GB			
Reset	Yes			
Alarm	No			
Intelligent Analytics				
Smart Event	Line crossing, region intrusion/entrance/exiting, loitering detection, illegal parking detection, abandoned/ missing object detection			
Statistics	Target counting by line/area, heat map			
Exception Detection	Scene change, video blur and abnormal color detection, audio exception			
Face Detection	Face detection and face capture			
Video Metadata	Simultaneously captures human body, motor vehicle and non-motor vehicle and extracts 13 human features, 4 motor vehicle features and 1 non-motor vehicle feature			
DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8~12mm(W)	85m(278ft)	34m(111ft)	17m(56ft)	8m(26ft)
2.8~12mm(T)	289m(948ft)	116m(380ft)	58m(190ft)	29m(95ft)
Functions				
Remote Monitoring	Web Browser, Viewtron VMS, NVR, Mobile app for iPhone, Android			
Web Browser	Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+			
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission			

Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTMP, RTCP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, HTTP POST, 802.1x, UPnP, HTTPS, P2P, QoS
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SMD, SD card error, SD card full, IP address conflict, Network disconnection, sensor alarm, audio alarm
General Function	Watermark, video mask, heartbeat, image distortion correction, corridor pattern, ANR, cloud upgrade
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP
PoE	Yes, IEEE802.3af
IR Distance	30 ~50 m
Ingress Protection	IP67
Others	
Power Supply	DC12V/PoE
Power Consumption	PoE: max. 9.7W; DC12V: max. 7.4W
Storage Conditions	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
Operating Conditions	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Ø 111.6 × 99.6
Weight (net)	Approx.0.67KG
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH(EC1907/2006)

DIMENSIONS



AVAILABLE ACCESSORIES



RECOMMENDED NVR

Viewtron IP camera NVRs are highly recommended for use with all Viewtron IP cameras. Viewtron NVRs are deeply integrated with Viewtron AI software functions and all IP camera management.

Learn more at www.Viewtron.com.